

TA / T

Type	Model	Nozzle Plug	Mounting type Ø (mm)	Rotation *		Nozzle Outlet *	Pressure Range (bar)	N.W. (1 Piece) (kg)
TA2	TA2A40107		F54	↻			7 - 40	5.6
TA2	TA2C40107		F54		↻		7 - 40	5.6
TA3	TA3A40107		F54	↻			7 - 40	5.8
TA3	TA3C40107		F54		↻		7 - 40	5.8
TA4	TA4A40107		F54	↻			7 - 40	6
TA4	TA4C40107		F54		↻		7 - 40	6
TA5	TA5A30107		F54	↻			7 - 30	6.3
TA5	TA5C30107		F54		↻		7 - 30	6.3
T2	T2A107		F70	↻			40 Max	7.7
T2	T2C107		F70		↻		40 Max	7.7
T3	T3A107		F70	↻			40 Max	8
T3	T3C107		F70		↻		40 Max	8
T4	T4A107		F70	↻			40 Max	8.6
T4	T4C107		F70		↻		40 Max	8.6
T5	T5A107		F70	↻			30 Max	9.3
T5	T5C107		F70		↻		30 Max	9.3

Seen from shaft end

- * shaft rotation
- right-hand nozzle outlet
- ← left-hand nozzle outlet
- for kerosene application
- ↻ clockwise rotation
- ↺ anti-clockwise rotation