

# TA / T

系列	型號	噴油塞子	連接方式及 輪穀 Ø (mm)	油泵轉向		噴油出口	壓力範圍	每只淨重 (kg)
TA2	TA2A40107		F54	↻			7 - 40	5.6
TA2	TA2C40107		F54		↻		7 - 40	5.6
TA3	TA3A40107		F54	↻			7 - 40	5.8
TA3	TA3C40107		F54		↻		7 - 40	5.8
TA4	TA4A40107		F54	↻			7 - 40	6
TA4	TA4C40107		F54		↻		7 - 40	6
TA5	TA5A30107		F54	↻			7 - 30	6.3
TA5	TA5C30107		F54		↻		7 - 30	6.3
T2	T2A107		F70	↻			40 Max	7.7
T2	T2C107		F70		↻		40 Max	7.7
T3	T3A107		F70	↻			40 Max	8
T3	T3C107		F70		↻		40 Max	8
T4	T4A107		F70	↻			40 Max	8.6
T4	T4C107		F70		↻		40 Max	8.6
T5	T5A107		F70	↻			30 Max	9.3
T5	T5C107		F70		↻		30 Max	9.3

從軸承末端觀看

- \* 軸承轉向
- ⇒ 噴油出口設于右方
- ⇐ 噴油出口設于左方
- 適合煤油使用
- ↻ 順時針轉向
- ↺ 逆時針轉向