

TA / T

| Type | Model | Nozzle Plug | Mounting type Ø (mm) | Rotation * | | Nozzle Outlet * | Pressure Range (bar) | N.W. (1 Piece) (kg) |
|------|-----------|-------------|-------------------------|------------|---|-----------------|----------------------|---------------------|
| | | | | | | | | |
| TA2 | TA2A40107 | | F54 | ↻ | | | 7 - 40 | 5.6 |
| TA2 | TA2C40107 | | F54 | | ↻ | | 7 - 40 | 5.6 |
| TA3 | TA3A40107 | | F54 | ↻ | | | 7 - 40 | 5.8 |
| TA3 | TA3C40107 | | F54 | | ↻ | | 7 - 40 | 5.8 |
| TA4 | TA4A40107 | | F54 | ↻ | | | 7 - 40 | 6 |
| TA4 | TA4C40107 | | F54 | | ↻ | | 7 - 40 | 6 |
| TA5 | TA5A30107 | | F54 | ↻ | | | 7 - 30 | 6.3 |
| TA5 | TA5C30107 | | F54 | | ↻ | | 7 - 30 | 6.3 |
| T2 | T2A107 | | F70 | ↻ | | | 40 Max | 7.7 |
| T2 | T2C107 | | F70 | | ↻ | | 40 Max | 7.7 |
| T3 | T3A107 | | F70 | ↻ | | | 40 Max | 8 |
| T3 | T3C107 | | F70 | | ↻ | | 40 Max | 8 |
| T4 | T4A107 | | F70 | ↻ | | | 40 Max | 8.6 |
| T4 | T4C107 | | F70 | | ↻ | | 40 Max | 8.6 |
| T5 | T5A107 | | F70 | ↻ | | | 30 Max | 9.3 |
| T5 | T5C107 | | F70 | | ↻ | | 30 Max | 9.3 |

Seen from shaft end

- * shaft rotation
- right-hand nozzle outlet
- ← left-hand nozzle outlet
- for kerosene application
- ↻ clockwise rotation
- ↺ anti-clockwise rotation